

2x1.5 mm² Flexible HFFR Speaker Cable

POWER & CONTROL

P/N 336152L101

INDUSTRY

Applications

Portable electrical equipment, Loudspeakers




Outer Jacket Material
HFFR



Outer diameter
8.2 mm nom.



Weight
103 kg/km



General Construction

2 - HFFR insulated 1.5 mm² flexible cores, cabled together and jacketed with a flexible HFFR compound.

Design & Materials

Conductor Material	Annealed Bare Copper
Conductor Cross Section (mm ²)	1.5
Conductor Construction	28x0.25 mm
Insulation Material	HFFR
Insulation Thickness (mm)	0.6
Insulation O.D. (mm nom)	2.90
Conductor Color Code	Blue, Red
Outer Jacket Thickness (mm nom)	1.0
Outer Jacket Color	Black
Marking	Per request

Performance

Max. DC Resistance (Ω/km@20°C)	13.3
Dielectric Strength (V/15 minutes)	2000
Voltage Rating (V)	400
Min. Operating Temperature (°C)	-40
Max. Operating Temperature (°C)	+90
UV Resistance	Yes

Standards

Flammability Rating
IEC 60332-1



Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Version 2.0 | Last update: 2017-10-26